

The JAG-PRD-415-07-4-RM four-cavity band-pass/band-reject duplexer is comprised of 7-inch aluminum cavities with internal silver-plated tuners to maintain a very high Q and low loss. As a consequence, the JAG-PRD-415-07-4-RM provides isolation in excess of 80dB at frequency separations of 2 MHz or greater.

The JAG-PRD-415-07-4-RM has been designed with temperature compensation in mind to avoid detuning and as a result, frequency drift over the operating temperature range is extremely small ($\cong 0.5$ ppm / degC).

Electrical Specifications	Mechanical Specifications	Environmental
Model JAG-PRD-415-07-4-RM	Model JAG-PRD-415-07-4-RM	Model JAG-PRD-415-07-4-RM
Frequency Range (MHz) 400 – 430	Height inches (mm) 18 (457)	Temperature Range -40-degC to +60-degC
Bandwidth @ 1.5:1 VSWR or Better (MHz) 20	Width inches (mm) 19 (483)	·
	Depth inches (mm) 15 (381)	
Maximum Input VSWR 1.5:1	Weight Ib (kg) 45 (20.4)	
Maximum Input Power (Watts) 200	Mounting System 19-inch rack mount	
Min Frequency Separation (MHz) 2.0		
Insertion Loss (dB) 2.2 – 2.5	Termination 'N' Female	
Isolation (dB) Tx noise suppression at Rx 80 min. Rx suppression at Tx 80 min. Port to Port 80 min.		
Nominal Impedance (Ω) 50		

Dated: March-17-2011

JAG-PRD-415-07-4-RM Product Specification Sheet.

Issue: 1

RF EMI Engineering Technology 26-1750 Creek Way Burlington, Ontario L7L 7E2 Canada Electromagnetics

Email: info@jagelectromagnetics.com Web: www.jagelectromagnetics.com Tel (905)-635-7437 Fax (905)-332-8093

Made in Canada

Rev031711.0

Page 1/1

JAG's dedication to continuous Research & Development will result in product improvements as they evolve.



Copyright © JAG Electromagnetics

